

Ручки

Ручка из чугуна, резьбовая шпилька из стали

ХАРАКТЕРИСТИКИ

Поворотная ручка



Чугун **SG**

Литьё с последующей чистовой обработкой

Резьбовая шпилька

Сталь

ввинчивается и фиксируется крестообразным штифтом



GN 6335.4

Описание	d ₁	d ₂	Длина l ≈	h ₁	h ₂	△
GN 6335.4-SG-32-M6-16	32	M 6	16	20	9	34
GN 6335.4-SG-32-M6-20	32	M 6	20	20	9	35
GN 6335.4-SG-32-M6-25	32	M 6	25	20	9	36
GN 6335.4-SG-32-M6-30	32	M 6	30	20	9	37
GN 6335.4-SG-32-M6-35	32	M 6	35	20	9	38
GN 6335.4-SG-32-M6-45	32	M 6	45	20	9	46
GN 6335.4-SG-40-M8-15	40	M 8	15	25	13	58
GN 6335.4-SG-40-M8-20	40	M 8	20	25	13	60
GN 6335.4-SG-40-M8-25	40	M 8	25	25	13	61
GN 6335.4-SG-40-M8-30	40	M 8	30	25	13	63
GN 6335.4-SG-40-M8-40	40	M 8	40	25	13	66
GN 6335.4-SG-40-M8-55	40	M 8	55	25	13	70
GN 6335.4-SG-50-M10-25	50	M 10	25	32	18	124
GN 6335.4-SG-50-M10-30	50	M 10	30	32	18	130
GN 6335.4-SG-50-M10-35	50	M 10	35	32	18	129
GN 6335.4-SG-50-M10-45	50	M 10	45	32	18	134
GN 6335.4-SG-50-M10-55	50	M 10	55	32	18	139
GN 6335.4-SG-63-M12-30	63	M 12	30	40	23	220
GN 6335.4-SG-63-M12-35	63	M 12	35	40	23	208
GN 6335.4-SG-63-M12-40	63	M 12	40	40	23	211
GN 6335.4-SG-63-M12-50	63	M 12	50	40	23	250
GN 6335.4-SG-63-M12-60	63	M 12	60	40	23	225
GN 6335.4-SG-80-M16-30	80	M 16	30	50	28	410
GN 6335.4-SG-80-M16-40	80	M 16	40	50	28	430
GN 6335.4-SG-80-M16-50	80	M 16	50	50	28	452
GN 6335.4-SG-80-M16-60	80	M 16	60	50	28	452
GN 6335.4-SG-80-M16-70	80	M 16	70	50	28	478